

Pipe clamps light version Fig. 3540

Light weight high stability because of reinforcement.

Available in mat. 1.4301 (scope of delivery doesn't include bolts & nuts)

The pipe clamps can also be used in slightly smaller pipe diameters (f.o. \varnothing 88.9 mm for pipe \varnothing 84 mm)

under consideration of a small tension loss.

Clamps for larger diameters only available acc. to DIN 3567

DN	d1	a	l	d2	f	b x s	100 pair~kg/ without bolts
15	20,0	50	70	9	4	35 x 1,5	5,70
15	21,3	52	72	9	4	35 x 1,5	5,80
20	25,0	55	75	9	4	35 x 1,5	6,00
20	26,9	57	77	9	4	35 x 1,5	6,00
25	30,0	60	80	9	4	35 x 1,5	6,50
25	33,7	65	85	9	4	35 x 1,5	7,00
32	38,0	69	89	9	4	35 x 1,5	7,50
32	42,4	73	93	11	4	35 x 1,5	8,00
40	44,5	75	95	11	4	35 x 1,5	8,30
40	48,3	80	100	11	4	35 x 1,5	8,80
50	57,0	92	112	11	4	35 x 1,5	10,0
50	60,3	94	114	11	4	35 x 1,5	11,0
65	76,1	118	140	11	6	40 x 2,5	25,0
80	88,9	135	157	11	6	40 x 2,5	28,0
100	104,0	145	167	11	6	40 x 2,5	33,0
100	108,0	156	178	11	6	40 x 2,5	34,0
100	114,3	158	180	11	6	40 x 2,5	35,0
125	133,0	183	211	13	6	50 x 2,5	52,0
125	139,7	190	218	13	6	50 x 2,5	54,0
150	159,0	210	238	13	6	50 x 2,5	60,0
150	168,3	218	246	13	6	50 x 2,5	62,0

