


Straight Female Coupling

Thread: DIN/ISO 228
Whitworth (zylindr.)



series	PN	Ra	G	d	S2	S1	L2	l2	weight %	article	
L	250	6	G 1/8	4	14	14	34	19,0	2,6	GAV-06LR 1/8	
		6	G 1/4	4	14	19	39	24,0	2,6	GAV-06LR 1/4	
		8	G 1/4	6	17	19	39	24,0	5,5	GAV-08LR 1/4	
		8	G 3/8	6	17	22	40	25,0	7,8	GAV-08LR 3/8	
		8	G 1/2	6	17	27	43	28	8,4	GAV-08LR 1/2	
		10	G 1/4	8	19	19	40	25,0	6,0	GAV-10LR 1/4	
		10	G 3/8	8	22	19	41	26	6,8	GAV-10LR 3/8	
		10	G 1/2	8	19	27	45	29	10,2	GAV-10LR 1/2	
		12	G 1/4	10	22	19	40	25,0	9,2	GAV-12LR 1/4	
		12	G 3/8	10	22	24	41	26,0	9,2	GAV-12LR 3/8	
		12	G 1/2	10	22	27	45	29,0	9,2	GAV-12LR 1/2	
		15	G 3/8	12	27	24	42	27,0	13,2	GAV-15LR 3/8	
		15	G 1/2	12	27	27	46	31,0	13,2	GAV-15LR 1/2	
		160	18	G 3/8	15	32	27	44	27,5	15,7	GAV-18LR 3/8
18			G 1/2	15	32	27	47	30,5	15,7	GAV-18LR 1/2	
		22	G 3/4	19	36	36	52	35,5	27,0	GAV-22LR 3/4	
100		28	G 1	24	41	41	55	38,0	31,1	GAV-28LR 1	
		35	G 1 1/4	30	50	55	63	41,0	42,0	GAV-35LR 1 1/4	
		42	G 1 1/2	36	60	60	65	42,5	60,5	GAV-42LR 1 1/2	
S	630	6	G 1/4	4	17	19	41	26,0	6,0	GAV-06SR 1/4	
		8	G 1/4	5	19	19	41	26,0	5,9	GAV-08SR 1/4	
		10	G 3/8	7	22	24	43	26,5	10,2	GAV-10SR 3/8	
		10	G 1/2	7	22	30	45	29,5	10,2	GAV-10SR 1/2	
		12	G 1/4	8	24	22	43	27,0	10,8	GAV-12SR 1/4	
		12	G 3/8	8	24	24	43	26,5	10,8	GAV-12SR 3/8	
		12	G 1/2	8	24	30	47	29,5	10,8	GAV-12SR 1/2	
		14	G 1/2	10	27	30	50	32,0	14,8	GAV-14SR 1/2	
		400	16	G 1/2	12	30	30	50	31,5	19,5	GAV-16SR 1/2
			20	G 3/8	16	36	32	49	27,5	30,7	GAV-20SR 3/8
			20	G 1/2	16	36	32	52	30,5	30,7	GAV-20SR 1/2
20	G 3/4		16	36	36	56	34,5	30,7	GAV-20SR 3/4		
	25	G 1	20	46	41	62	37,5	46,6	GAV-25SR 1		
250	30	G 1 1/4	25	50	55	69	42,0	74,1	GAV-30SR 1 1/4		
	38	G 1 1/2	32	60	60	74	43,5	85,5	GAV-38SR 1 1/2		

