



Adjustable Elbow Coupling

With male stud coupling DIN/ ISO 228

series	PN	Ra	G	i	d3	S2	S1	S3	I3	L2	l2	weight %	article
L	250	6	G 1/8 A	8	14	14	12	14	35,0	29	14,0	5,7	EWV-06LR 1/8
		8	G 1/4 A	12	18	17	12	19	37,5	29	14,0	8,2	EWV-08LR 1/4
		10	G 1/4 A	12	18	19	14	19	40,0	30	15,0	9,6	EWV-10LR 1/4
		12	G 3/8 A	12	22	22	17	22	42,0	32	17,0	13,4	EWV-12LR 3/8
		15	G 1/2 A	14	26	27	19	27	46,5	36	21,0	22,9	EWV-15LR 1/2
	160	18	G 1/2 A	14	26	32	24	27	50,0	40	23,5	30,5	EWV-18LR 1/2
		22	G 3/4 A	16	32	36	27	32	55,0	44	27,5	41,5	EWV-22LR 3/4
		100	28	G 1 A	18	39	41	36	41	59,0	47	30,5	61,4
	35		G 1 1/4 A	20	49	50	41	50	69,0	56	34,5	98,5	EWV-35LR 1 1/4
		42	G 1 1/2 A	22	55	60	50	55	75,0	63	40,0	141,7	EWV-42LR 1 1/2
S	630	6	G 1/4 A	12	18	17	12	19	40,0	31	16,0	9,9	EWV-06SR 1/4
		8	G 1/4 A	12	18	19	14	19	43,0	32	17,0	12,1	EWV-08SR 1/4
		10	G 3/8 A	12	22	22	17	22	45,0	34	17,5	16,9	EWV-10SR 3/8
		12	G 3/8 A	12	22	24	17	22	48,0	38	21,5	20,2	EWV-12SR 3/8
		14	G 1/2 A	14	26	27	19	27	54,0	40	22,0	28,7	EWV-14SR 1/2
	400	16	G 1/2 A	14	26	30	24	27	54,0	43	24,5	33,9	EWV-16SR 1/2
		20	G 3/4 A	16	32	36	27	32	65,0	48	26,5	55,1	EWV-20SR 3/4
		25	G 1 A	18	39	46	36	41	73,0	54	30,0	105,4	EWV-25SR 1
	250	30	G 1 1/4 A	20	49	50	41	50	79,0	62	35,5	139,8	EWV-30SR 1 1/4
		38	G 1 1/2 A	22	55	60	50	55	89,0	72	41,0	194,4	EWV-38SR 1 1/2

