


Male/Female Stud Adaptor, Short Form

DIN/ISO 228
Whitworth



PN	G1	G2	i	S1	d3	l	t	weight %	article
630	G 3/8 A	G 1/8	12	22	22	22,5	8	4,0	RIG 3/8x1/8
	G 1/2 A	G 1/8	14	27	26	24,0	8	5,7	RIG 1/2x1/8
400	G 1/2 A	G 1/4	14	27	26	24,0	12	5,7	RIG 1/2x1/4
	G 3/4 A	G 1/4	16	32	32	26,0	12	10,4	RIG 3/4x1/4
	G 3/4 A	G 3/8	16	32	32	26,0	12	8,7	RIG 3/4x3/8
	G 1 A	G 1/4	18	41	39	29,0	12	20,0	RIG 1 x1/4
	G 1 A	G 3/8	18	41	39	29,0	12	18,7	RIG 1 x3/8
250	G 1 A	G 1/2	18	41	39	29,0	14	14,7	RIG 1 x1/2
	G 1 1/4 A	G 1/2	20	50	49	32,0	14	31,7	RIG 1 1/4x1/2
	G 1 1/4 A	G 3/4	20	50	49	32,0	16	26,4	RIG 1 1/4x3/4
	G 1 1/2 A	G 1/2	22	55	55	36,0	14	47,0	RIG 1 1/2x1/2
	G 1 1/2 A	G 3/4	22	55	55	36,0	16	42,7	RIG 1 1/2x3/4
	G 1 1/2 A	G 1	22	55	55	36,0	18	34,2	RIG 1 1/2x 1

