



Hexagon bushing 418

EN 10241 / DIN 2990 AISI 3161 investment casting

dimension R-DIN 2999xRp	L mm	SW	weight/pcs
1/4"x 1/8"	17	15	0,01
3/8"x 1/4"	17	18	0,02
3/8"x 1/8"	17	18	0,02
1/2"x 3/8"	20	22	0,04
1/2"x 1/4"	20	22	0,04
1/2"x 1/8"	20	22	0,04
3/4"x 1/2"	24	28	0,07
3/4"x 3/8"	24	28	0,07
3/4"x 1/4"	24	28	0,07
3/4"x 1/8"	24	28	0,07
1"x 3/4"	25	35	0,08
1"x 1/2"	25	35	0,10
1" x 3/8"	25	35	0,10
1" x 1/4"	25	35	0,10
1 1/4"x 1"	29	44	0,12
1 1/4"x 3/4"	29	44	0,16
1 1/4"x 1/2"	29	44	0,18
1 1/4"x 3/8"	29	44	0,18
1 1/2"x 1 1/4"	29	49	0,14
1 1/2"x 1"	29	49	0,20
1 1/2"x 3/4"	29	49	0,22
1 1/2"x 1/2"	29	49	0,24
2"x 1 1/2"	34	62	0,29
2"x 1 1/4"	34	62	0,31
2"x 1"	34	62	0,40
2"x 3/4"	34	62	0,44
2"x 1/2"	34	62	0,48
2 1/2"x 2"	37	78	0,49
2 1/2"x 1 1/2"	37	78	0,60
2 1/2"x 1 1/4"	37	78	0,67
3"x 2 1/2"	43	90	0,62
3"x 2"	43	90	0,91
3"x 1 1/2"	43	90	1,05

